


## APPLI CATION:

Suitable for heavy cutting with milling machine, shaper, planer, etc.

## **FEATURES:**

Specially designed for heavy cutting. The gap between magnetic poles is enlarged and magnetic forced is super powerful. Excellent for powerful attraction of the work piece with thickness of 15m/m or thicker and size in 100x100m/m or larger.

Drag magnetic force, average 18 kgf magnetic attraction



Unit:mm

Order No.	Model	Nominal Dimension	Chuck Dimension				Pole Pitch	Rotary Base			н	N.W.	Vollage	Current
			B1	L1	Le	t	P	B <sub>2</sub>	L2	h	NACT OF	(kg)	(Dcv)	(A)
34080-05	ELC-820Z	200x 500	200	500	437	20	35 (8+27)	200	550	18	118	79	90	1.28
34080-10	ELC-824Z	200x 600	200	600	533				650	18	118	94	90	1.97
34080-15	ELC-832Z	200x 800	200	800	743				850	18	118	125	90	2.72
34080-20	ELC-1020Z	250x 500	250	500	437			250	550	20	120	98	90	1.82
34080-25	ELC-1024Z	250x 600	250	600	533				650	20	120	117	90	2.18
34080-30	ELC-1224Z	300x 600	300	600	533			300	650	20	120	140	90	2.44
34080-35	ELC-1236Z	300x 900	300	900	854				950	20	120	210	90	3.56
34080-40	ELC-1632Z	400x 800	400	800	743			400	850	20	120	250	90	4.4
34080-45	ELC-1640Z	400x1000	400	1000	931				1050	20	120	315	90	5
34080-50	ELC-2040Z	500x1000	500	1000	931		42 (8+34)	500	1050	23	123	400	90	6.01
34080-55	ELC-2060Z	500x1500	500	1500	1443				1550	23	123	600	90	10.4
34080-60	ELC-2440Z	600x1000	600	1000	931			600	1050	25	125	480	90	7.4
34080-65	ELC-2460Z	600x1500	600	1500	1443				1550	25	125	735	90	10.7