



- Used for balancing purpose.
- Compact design.
- Strong Rare Earth magnets.
- One side magnetic face.
- Weight is engraved

Cat No.	Capacity
UL-40601	5 gms - 2 kg



Used in Automated manufacturing lines as the magnetic force can be turned on & off or increased or decreased by remote operation via a rectifier or PLC.

Features -

- Electrical Control can be used for turning on & off the magnetic force.
- Usable for continuous operation.
- Quick Attach & Detach enables speedy automation.

Applications -

- Automated press.
- Prevention of deflection for shearing material.
- Various automatic processes.
- Holding Hands of Industrial robots.
- In Machine shop, Press Shop, Assembly Line Material Feed.

Sr. No.	Cat No.	Size (mm)	Max Holding Power	Working Voltage
1.	UL - 82601	Ø 30 x 40 H	3kg	24 DC
2.	UL - 82602	Ø 30 x 25 H	2kg	24 DC
3.	UL - 82603	Ø 35 x 30 H	8kg	24 DC
4.	UL - 82604	Ø 30 x 45 H	15kg	24 DC
5.	UL - 82605	Ø 40 x 45 H	35kg	24 DC
6.	UL - 82606	Ø 50 x 30 H	40kg	24 DC
7.	UL - 82607	Ø 90 x 65 H	160kg	24 DC

"ULTRA" CONTROL UNIT

Special Sizes Available on Request as per Application.



- Useful in workshops, Garage, Assembly shops for keeping various hand tools.
- Compact design with strong magnetic field.
- Protected from rust & corrosion.
- Can also be used for small lifting & holding.
- Easy for handling & storage.

Cat No.	Size (mm)
UL - 70601	150 L x 25 W x 30 H
UL - 70602	225 L x 25 W x 30 H
UL - 70603	300 L x 25 W x 30 H